




# EMGE®

## ASEL

Led Canopy



LED TECHNOLOGY INCLUDED

INVENTRONICS

SAMSUNG

NICHIA

OSRAM

MW  
MEAN WELL

Teknik Özellikler / Technical Specifications

<b>Gövde</b>	<b>Elektrostatik Toz Boyalı DKP Saç Ve Alüminyum Soğutucu</b>
Body	Electrostatic Powder Coated DKP Sheet And Aluminum Heatsink
<b>Montaj</b>	<b>Sıvaaltı</b>
Mounting	Recessed
<b>Renk</b>	<b>Standart (Beyaz)</b>
Color	Standart (White)
<b>Cam</b>	<b>4mm Temperli Cam</b>
Diffuser	4mm Tempered Glass
<b>LED Ömrü</b>	<b>(L80B10) &gt;72.000 Saat</b>
LED Lifetime	>72.000 Hours
<b>Sürücü</b>	<b>&gt;100000 Saat Ömür, Verimlilik &gt;92, PFC &gt;95</b>
Driver	Lifetime >100000, Efficiency >92, PFC >95
<b>Giriş Voltajı</b>	<b>140-305 V , 50-60 Hz</b>
Input Voltage	140-305 V , 50-60 Hz
<b>Optik</b>	<b>18° - 40° - 60° - 90° - 140°/60° Asimetrik</b>
Optic	18° - 40° - 60° - 90° - 140°/60° Asymmetric
<b>Led</b>	<b>Yüksek Etkinlik Faktörüne Sahip Mid-Power</b>
Led	High Efficiency Mid-Power



Tip Type	Güç Power	Renk Sıcaklığı Color Temperature	Işık Akısı Luminous Flux			CRI	Ağırlık Weight (kg)
			Eko	Standart	pro		
LEDASL	75W	3000K-4000K-5000K-6500K	7501 LM	8625 LM	9750 LM	>80	6,5

